



CLEVIS HANGER & SPRINKLER CLAMP

DIAMOND WALRAVEN BRAND



Light Duty Sprinkler Clamps



Features and benefits


- Suitable for fire fighting installations
- Single piece design capable of carrying high load
- Unique design accomodates high water pressure
- To be installed with thread rods and nuts on either side of clamp

Technical Data

- Electrogalvanized as per ASTM B633

Part No.	D (mm)	D (")	G	h (mm)	b x s (mm)	Fa.z Appr. (kgs)
DMC757028	28	3/4	M10	61	20 x 1.0	2,500
DMC757035	35	1	M10	68	20 x 1.0	2,500
DMC757040	42	1 1/4	M10	75	20 x 1.0	2,500
DMC757048	48	1 1/2	M10	81	20 x 1.0	2,500
DMC757060	60	2	M10	100	20 x 1.0	2,500
DMC757075	73	2 1/2	M10	120	20 x 1.5	3,000
DMC757090	89	3	M10	135	20 x 1.5	3,000
DMC757100	105	3 1/2	M10	150	20 x 1.5	3,000
DMC757115	115	4	M10	165	20 x 1.5	3,000
DMC757140	140	5	M12	195	32 x 2.0	3,000
DMC757168	168	6	M12	230	32 x 2.0	4,000
DMC757200	219	8	M12	290	32 x 2.0	4,000
DMC757250	273	10	M12	315	32 x 2.0	5,000

Measurements are subject to 5% tolerance



Subject to modifications

Light Duty Clevis Hanger



Features and benefits


- Suitable for chilled water and fire fighting installations
- Pipe adjustment after installation possible
- To be installed with threaded rod and nuts on either side of upper portion

Technical Data

- Material: Mild Steel
Electrogalvanized as per ASTM B 633

Part No.	D (mm)	D (")	Bolt (mm)	H (mm)	b (mm)	s (mm)	s1 (mm)	d1 (mm)	Fa,z Appr. (kgs)
DMC999022	22	½	M8x60	70	20	1.6	1.6	10	2,500
DMC999028	28	¾	M8x68	76	20	1.6	1.6	10	2,500
DMC999035	35	1	M8x78	82	20	1.6	1.6	10	2,500
DMC999040	42	1 ¼	M8x82	92	20	1.6	1.6	10	2,500
DMC999048	48	1 ½	M8x88	100	20	1.6	1.6	10	2,500
DMC999060	60	2	M8x110	117	20	1.6	1.6	10	2,500
DMC999075	73	2 ½	M10x125	146	25	2	2	10	3,000
DMC999090	89	3	M10x140	155	25	2	2	10	3,000
DMC999105	105	3 ½	M10x155	173	25	2	2	10	3,000
DMC999115	115	4	M10x170	198	25	2	2	10	3,000
DMC999140	140	5	M12x195	232	25	2	2	10	3,000
DMC999168	168	6	M12x225	266	25	2.5	2.5	12	4,000
DMC999219	219	8	M12x275	338	25	2.5	2.5	12	4,000
DMC999273	273	10	M12x360	419	25	2.5	2.5	12	4,000
DMC999323	323	12	M16x420	490	25	4	4	12	5,500
DMC999355	355	14	M16x456	556	25	4	4	12	5,500
DMC999406	406	16	M20x510	610	32	6	6	14	12,000
DMC999457	457	18	M20x555	675	32	6	6	14	12,000
DMC999508	508	20	M20x610	715	40	6	6	14	15,000
DMC999610	610	24	M24x710	850	40	6	6	14	15,000
DMC999755	755	30	M24x890	995	40	6	6	14	15,000

Measurements are subject to 5% tolerance



Subject to modifications

CERTIFICATE OF REGISTRATION

This is to certify that the management system of:

Hira Walraven AC Industry LLC

Main Site: Plot of Land TP030201A, P.O Box No. 241579,
Techno Park / National Industries Park,
Dubai, United Arab Emirates

has been registered by Intertek as conforming to the requirements of:

ISO 9001:2015

The management system is applicable to:

Manufacture of Diamond Walraven pipe support systems.

Certificate Number:
0155495

Initial Certification Date:
25 August 2023

Date of Certification Decision:
25 August 2023

Issuing Date:
25 August 2023

Valid Until:
24 August 2026



A handwritten signature in black ink, appearing to read 'Calin Moldovean'.

Calin Moldovean
President, Business Assurance

Intertek Certification Limited, 10A Victory Park,
Victory Road, Derby DE24 8ZF, United Kingdom

Intertek Certification Limited is a UKAS
accredited body under schedule of
accreditation no. 014.



In the issuance of this certificate, Intertek assumes no liability to any party other than to the Client, and then only in accordance with the agreed upon Certification Agreement. This certificate's validity is subject to the organization maintaining their system in accordance with Intertek's requirements for systems certification. Validity may be confirmed via email at certificate.validation@intertek.com or by scanning the code to the right with a smartphone. The certificate remains the property of Intertek, to whom it must be returned upon request.

