



UPVC Solvent Cement

Product Description

- Low VOC
- For potable water, plumbing, irrigation, conduit sewer, drain, waste and vent systems.
- Store in ventilated area

Form: Liquid	Color: transparent	Color: transparent
P.H. Value:	Boiling Range: 77 °C based on Ethyl acetate	Decomposition Temperature:
Specific Gravity: 0.95	Solubility in water: incompletely soluble	Flash Point: -4.4°C based on Ethyl acetate
Vapor Pressure: 75 mmHg ethyl acetate	Explosion Limits: LEL:1.1% based on Cyclohexanone	Explosion Limits: UEL:11.5% based on Ethyl acetate

Method of Application

1. Cut pipes equally.
2. Clean both surface with dry cloth.
3. Insert pipe in fitting and mark.
4. Apply an even layer of cement.
5. Push the pipe into the socket with a minimal twisting motion. Hold securely for a few moments.
6. Remove excess cement in pipe.

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces-No Smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face Protection. Store in a well ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local regulation. Keep out of reach of children



INTELLECTUAL PROPERTY
OFFICE OF THE PHILIPPINES

Certificate of Registration

Registration No. : 4/2021/00502839
Date of Registration : 13 January 2022
Term : 10 years (until 13 January 2032)



FILMAX SOLVENT CEMENT

Filing Date : 5 February 2021
Registrant : BG FILMACO VENTURE CORPORATION [PH]
Address : 32 Road 12 St. FCI Warehouse, NDC Compound, Pureza,
Sta.Mesa, Manila 1016, Metro Manila, Philippines
Class(es) - Goods/Services : Class 1: Adhesives for the construction industry
Claim of Color(s) : Dark Blue
Disclaimer : Solvent Cement
Transliteration / Translation : None
Three-dimensional : No
Claim of Priority : None
Published for Opposition : IPO e-Gazette, published on 13/12/2021

JESUS ANTONIO Z. ROS
Director
Bureau of Trademarks

Digitally Signed by IPO Philippines
05/04/2022